

Your partner for innovative cleaning solutions



Numafa, your partner for innovative cleaning solutions.

We develop, manufacture and deliver innovative industrial cleaning solutions for the food and non-food industry since 1977. With offices in the Netherlands and America, we ship to every continent. In addition, we provide full maintenance and service.



Numafa Cleaning & Automation B.V.

+31 (0)186 65 08 50 • info@numafa.com • www.numafa.com
Sikkel 1, 3274 KK Heinenoord, The Netherlands

Your partner for innovative cleaning solutions



Discover the PWM GO

Clean, Smart, Reliable.



PWM GO

Compact Power for Pallet and Lid Cleaning

The PWM Go is a compact, energy-efficient pallet washer designed to deliver powerful cleaning performance while saving water and energy. Its intelligent water recirculation system ensures optimal use of resources, making it an ecological solution for modern production environments.

Designed for seamless integration into continuous transport systems, the PWM Go features a clear infeed and outfeed side. Pallets move smoothly through the washing tunnel past adjustable spray pipes with fixed nozzles, ensuring thorough cleaning from all angles.

With a variable transport speed, adjustable on the frequent controller, the PWM Go easily adapts to your workflow. The spray pipes are equipped with quick couplings and numbered for easy removal and maintenance — ensuring minimal downtime and maximum hygiene.

For even greater operator comfort, the PWM Go is available with an ergonomically lowered infeed.

- ✓ **Outstanding** cleaning performance
- ✓ **Low** operating costs
- ✓ **Industrial-Grade** durability (15-20 years)
- ✓ **Modular** design
- ✓ **Easy** to operate & maintain



Technical data

Material	Stainless steel 304
Capacity	Up to 100 per hour
Measurements machine (closed)	4.500 x 1.390 x 2.120 mm (LxWxH)
Transport chain	Stainless steel 316 Ø 10mm
Tank volume	500 liters
Filtration	Sieve plate 2 mm
Electric heating	27 kW (3x9kw) 15-45°C
Fresh water rinsing	100-250 l/h
Work height	670 mm
Product limits	260 x 1300 mm (WxH)

Options

- ✓ Alternative heating (steam injection)
- ✓ Vapor extraction
- ✓ Extra heating element (50°C)
- ✓ Chemical dosing pump
- ✓ Ergonomically lowered pallet infeed

